

Technical Bulletin GT-Touring Endurance n°4

Bulletin technique GT-Touring Endurance n°4

Purpose : modification of 308 Racing Cup Technical Regulation :

Following the manufacturer's request, the following articles of the technical regulations of the 308 Cup are amended as such:

8.3 – Springs

Only the use of the front and rear suspension springs listed below is authorized:

FRONT

| | | | |
|------------|---|------------------------------|---------------------------------|
| 1E1410257A | 2 | Ressort AV 10 daN/mm (Jaune) | Front spring 10 daN/mm (Yellow) |
| 1E1410258A | 2 | Ressort AV 11 daN/mm (Rouge) | Front spring 11daN/mm (Red) |

REAR

| | | | |
|------------|---|-----------------------------------|---------------------------------------|
| 1E2520123A | 2 | Ressort AR 7 daN/mm (Rouge Clair) | Rear main spring 7 dan/mm (Light red) |
| 1E2520124A | 2 | Ressort AR 7.7 daN/mm (Vert) | Rear main spring 7.7 dan/mm (Green) |

The springs must be of identical stiffness on the same axle. The springs must keep their original color.

8.5 – Front Anti-roll Bar

Only the front anti-roll bars listed below are allowed:

| | | |
|------------|---|--|
| 9802704080 | 1 | FRONT ANTI ROLL BAR BARRE DIAMETER 21 |
| 9802704280 | 1 | FRONT ANTI ROLL BAR BARRE DIAMETER 22 |
| 9802704380 | 1 | FRONT ANTI ROLL BAR BARRE DIAMETER 22.45 |

It is authorized to disconnect the front anti-roll bar provided that the front right connecting rod and the 2 fixing bolts of this rod are removed.

Objet : Modification du règlement technique de la 308 Racing Cup

A la demande du constructeur, les articles suivants du règlement technique de la 308 Cup sont modifiés comme tel :

8.3 - Ressorts de suspension

Seule l'utilisation des ressorts de suspension avant et arrière listés ci-dessous est autorisée :

AVANT

| | | | |
|------------|---|------------------------------|---------------------------------|
| 1E1410257A | 2 | Ressort AV 10 daN/mm (Jaune) | Front spring 10 daN/mm (Yellow) |
| 1E1410258A | 2 | Ressort AV 11 daN/mm (Rouge) | Front spring 11daN/mm (Red) |

ARRIERE

| | | | |
|------------|---|-----------------------------------|---------------------------------------|
| 1E2520123A | 2 | Ressort AR 7 daN/mm (Rouge Clair) | Rear main spring 7 dan/mm (Light red) |
| 1E2520124A | 2 | Ressort AR 7.7 daN/mm (Vert) | Rear main spring 7.7 dan/mm (Green) |

Les ressorts doivent être de raideurs identiques sur un même essieu. Les ressorts doivent conserver leur couleur d'origine.

8.5 – Barre Antiroulis avant

Seules les barres antiroulis avant listées ci-dessous sont autorisées :

| | | |
|------------|---|-------------------------------------|
| 9802704080 | 1 | BARRE ANTI DEVERS AV DIAMETRE 21 |
| 9802704280 | 1 | BARRE ANTI DEVERS AV DIAMETRE 22 |
| 9802704380 | 1 | BARRE ANTI DEVERS AV DIAMETRE 22.45 |

Il est autorisé de déconnecter la barre antiroulis avant à condition que la biellette de connexion avant droite et les 2 boulons de fixation de cette biellette soient retirés.